

CERTIFICATE OF CALIBRATION

HYTORC TECHNOLOGIES GMBH
KLEINBECKSTRASSE 3-17
SPROCKHOEVEL, D-45549, Germany
Cell: +49 2324 84793 0

MANUFACTURER HYTORC
TOOL MODEL LST-3000
STATED ACCURACY $\pm 5\%$

SERIAL # 17260007D
ASSET # N/A

SETTINGS RANGE 500 to 3.000

PROCEDURE AND METHOD USED

The Electric Torque Tool was calibrated on Torque Specialties TORQUE MASTER Automated Hydraulic Calibration System, in accordance with

CALIBRATION EQUIPMENT USED

Torque Specialties TORQUE MASTER Automated Hydraulic Calibration System

[X] TSD20011, s/n 8260, 0 to 20000 ft.lb. Torque Cell with TSD6500-3 s/n 21326 Instrument, NIST Traceability Reference # 166170, Calibration Date: 03.04.2026, Calibration Due Date 03.2027, Accuracy within ± 0.25 Indicated Value.

Tool is calibrated at intervals indicated. Type of Joint: Low Torque-Rate per SOP-0522-1

Calibration performed at Temperature 23°C Relative Humidity 26%

Standard Torque

Screen Settings	MIN Torque [Lb.ft (N.m)]	MAX Torque [Lb.ft (N.m)]	As Received / As Left Torque
500	475 (644)	525 (712)	498 (675) ✓
1,125	1,068 (1,448)	1,181 (1,601)	1,122 (1,521) ✓
1,750	1,662 (2,253)	1,837 (2,491)	1,744 (2,365) ✓
2,375	2,256 (3,059)	2,493 (3,380)	2,362 (3,202) ✓
3,000	2,850 (3,864)	3,150 (4,271)	3,068 (4,160) ✓

HYTORC-Hustach

ZA Chemin de Montépy
69210 FLEURIEUX SUR L'ARBRESLE

Tél. : 04 78 33 39 19

E-mail : sn@hytorc-ce.com

N° SIRET : 808 881 189 00019

TVA : FR 11 808 881 189

Inspection Checks Done, Reverse, High Speed & Trq Angle: PASSED ✓

As Received / As Left Calibration PASSED ✓

CALIBRATED BY: Manuel Röseler

CERTIFICATE #: 1-260504093110

CALIBRATION INTERVAL: 1 Year

CALIBRATION DUE DATE: May 4, 2027

UNCERTAINTY: 1% of reading

APPROVED BY: Per Wiemer
Lab Manager

CALIBRATION DATE: May 4, 2026

ISSUE DATE: May 4, 2026

DATE TOOL PUT IN SERVICE: Oct-09-2026

Calibrations are in accordance with requirements of ISO/IEC 17025:2017. Calibration results were obtained using equipment capable of producing results that are traceable to NIST and through NIST to the International System of Units (SI). Expanded uncertainties expressed at approximately 95% confidence levels using a coverage factor K=2 was accounted for in making compliance/non compliance decision with specification, and are available upon request within 30 days of calibration date. Results are valid only to the above item calibrated at the time of test. This certificate shall not be reproduced except in full without the written permission of HYTORC TECHNOLOGIES GMBH. Pass/Fail results are based on +/- tolerance only. Many factors may cause an item to drift out of tolerance before the next scheduled calibration.

(created with HY-Cal-D v1.6.2)